2018 MODEL SPECIFICATIONS

SERIES	FRONTIER	FRONTIER	FRONTIER	FRONTIER	FRONTIER	FRONTI
VEHICLE	6x6 SE	6x6 SCOUT S	6x6 ST LE	8x8 S	8x8 SCOUT S	8x8 S L
Engine	Kohler Command Pro	Kohler Command Pro	Kohler Command Pro	Kohler Command Pro	Kohler Command Pro	Kohler Comma
Engine Warranty	3 year	3 year	3 year	3 year	3 year	3 year
Type	4 cycle OHV gasoline-powered engine features electronic fuel injection (EFI), full pressure lubrication and V-twin cylinders.					
Horsepower[1]	23	23	23	23	26	26
Displacement	747 cc	747 cc	747 cc	747 cc	747 cc	747 cc
Cooling	Air Cooled	Air Cooled	Air Cooled	Air Cooled	Air Cooled	Air Coole
Alternator	--------	Optional	Optional	Optional	Optional	Optiona
Service Brakes	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical	Mechanic
Steering Brakes	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydrauli
Brake Cooling Fan	Optional	Optional	Optional	Standard	Standard	Standar
Steering	One-piece, ergonomic handlebar. Steering control features hand brake. For safety and ease of handling, the ARGO steering transmission provides continuous torque to all a					
Controls	Right-hand twist grip throttle. Dash mounted light and ignition switch.					
Clutch	Belt-driven, Continuously Variable Transmission (CVT) maximizes engine power to the transmission.					
Transmission	CLASSIC[2]	CLASSIC[2]	ADMIRAL[3]	CLASSIC[2]	CLASSIC[2]	CLASSIC
Transmission Options	STD	STD or HT	STD	STD or HT	STD or HT	STD or H
Drive System	Chain drive to machined sprockets. 1 1/4" diameter axles with triple sealed greaseable outer bearings.					
Final Drive	RC60 roller chain drive to all 6 axles.			RC50-2 and RC60 roller chain drive to all 8 axles.		
HD Drive Belt	Optional	Optional	Optional	Standard	Standard	Standar
Frame	Formed steel channel frame, welded for high strength and durability. Protected with Bonderite® epoxy-acrylic base coat, textured black epoxy top coat.					
Body	Vacuum formed High Molecular Weight Polyethylene (HMWPE) on-piece lower body.					
Full Skid Plate	Standard	Standard	Standard	Standard	Standard	Standar
Brushguard	Optional	Standard	Standard	Optional	Standard	Standar
Winch	Optional	3,500 lb. Warn Winch	3,500 lb. Warn Winch	Optional	3,500 lb. Warn Winch	3,500 lb. Warn
Bilge Pump	Standard	Standard	Standard	Standard	Standard	Standar
Load Capacity[4] – On Land[5]	640 lb. (290 kg)	560 lb. (254 kg)	560 lb. (254 kg)	910 lb. (413 kg)	830 lb. (376 kg)	830 lb. (358
Load Capacity[4] – Rear Compartment	140 lb. (64 kg)	140 lb. (64 kg)	140 lb. (64 kg)	140 lb. (64 kg)	--------	--------
Load Capacity[4] – On Water	440 lb. (200 kg)	360 lb. (163 kg)	360 lb. (195 kg)	810 lb. (367 kg)	730 lb. (331 kg)	730 lb. (358
Towing Capacity[6]	1,200 lb. (544 kg)	1,200 lb. (544 kg)	1,200 lb. (544 kg)	1,400 lb. (635 kg)	1,400 lb. (635 kg)	1,400 lb. (63
Seating Capacity[7] – On Land	4 persons	4 persons	4 persons	6 persons	6 persons	6 person
Seating Capacity[7] – On Water	2 persons	2 persons	2 persons	4 persons	4 persons	4 person
Fuel Capacity	7.1 US gallons (27 litres) See-through polyethylene fuel tank. 8 hrs. operation.[8]					
Speed[9] – On Land	22 mph (35 km/h)	22 mph (35 km/h)	22 mph (35km/h)	19 mph (30 km/h)	19 mph (30 km/h)	19 mph (30 k
Speed[9] – On Water[10]	3 mph (5 km/h)	3 mph (5 km/h)	3 mph (5 km/h)	3 mph (5 km/h)	3 mph (5 km/h)	3 mph (5 km
Shipping Weight	910 lb. (413 kg)	990 lb. (449 kg)	990 lb. (417 kg)	1,140 lb. (517 kg)	1,220 lb. (553 kg)	1,220 lb. (57
Dimensions (L X W X H) (inch)	95 x 58 x 45.8	102 x 58 x 52.5	102 x 58 x 52.5	119 x 58 x 46.5	124 x 58 x 52	124 x 58 x
Dimensions (L X W X H) (mm)	2,413 x 1,473 x 1,163	2,591 x 1,473 x 1,334	2,591 x 1,473 x 1,334	3,023 x 1,473 x 1,181	3,150 x 1,473 x 1,321	3,150 x 1,473 x
Axle Bearing Extensions	Standard	Standard	Standard	Standard	Standard	Standar
Instrumentation	LCD digital gauge cluster: speedometer, odometer, voltmeter, hour meter, tachometer, low oil pressure, parking brake reminder lights and check engine light.					
Entry Step	Standard	Standard	Standard	Optional	Standard	Standar
Tires	ARGO AT189 24x10.0-8 NHS					
Ground Pressure	2.5 psi (17.2 kPa) using tires					
Ground Clearance – Tires	9.5" (240 mm)	9.5" (240 mm)	9.5" (240 mm)	9.5" (240 mm)	9.5" (240 mm)	9.5" (240 m
Ground Clearance – Tracks	10.5" (265 mm)	10.5" (265 mm)	10.5" (265 mm)	10.5" (265 mm)	10.5" (265 mm)	10.5" (265 m
Operating Conditions	All weather, all terrain, -40°F to +104°F (-40°C to +40°C)					
Warranty	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year
Color Options						