Minnesota Unique Well Number

561568

County Wright
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH WELL AND BORING REPORT

Minnesota Statutes Chapter 1031

Entry Date Update Date 05/09/1997 02/14/2014

HE-01205-15

Received Date

CLAY	Status Active To le Diameter in. To 50 ft. ft. NSON
Use	To le Diameter in. To 50 ft. ft. NSON ft.
Well	To le Diameter in. To 50 ft. ft. NSON ft.
Contact 125 PARK ST E ANNANDALE MN 55302 Casing Type Single casing Joint	le Diameter in. To 50 ft. ft. NSON ft.
Drive Shoe2 Ves No	ft. SON ft.
Casing Diameter Weight Bio	ft. SON ft.
CLAY	ft. SON ft.
CRAVEL 6	ft. ISON ft.
CLAY ROCKY	ft.
SAND 15- 30 GRAVEL 38 50 ORN/BRN MEDIUM Open Hole From ft. To Screen? Type stainless Make JOHN Diameter Slot/Gauze Length Set 12 in. 35 20 ft. 30 ft. 50 Static Water Level 14 ft. land surface Pumping Level (below land surface) 22 ft. 7 hrs. Pumping at 300 g.p.m. Wellhead Completion Pitless adapter manufacturer Armount Fro Argrade (Environmental Wells and Borings ONLY) Grouting Information Well Grouted? Maeterial Armount Fro bentonite 6 Sacks 0 Nearest Known Source of Contamination 200 feet East Direction X yes No Material Armount Fro bentonite 6 Sacks 0 Nearest Known Source of Contamination 200 feet East Direction X yes Manufacturer Well disinfected upon completion? X yes No Manufacturer's name WESTERN Manufacturer's name WESTERN Model Manufacturer's name MESTERN Model Manufactur	ft.
Open Hole From ft. To	ft.
Screen? Type stainless Make JOHN Diameter Slot/Gauze Length Set 12 in. 35 20 ft. 30 ft. 50 Static Water Level 14 ft. land surface Measure 04 Pumping Level (below land surface) 22 ft. 7 hrs. Pumping at 300 g.p.m. Wellhead Completion 12 in. above grade Model Casing Protection 12 in. above grade At-grade (Environmental Wells and Borings ONLY) Grouting Information Well Grouted? Yes No Material Amount Fro bentonite 6 Sacks 0 Nearest Known Source of Contamination 200 feet East Direction Septic ta Well disinfected upon completion? Yes Yes Pump	ft.
Diameter Slot/Gauze Length Set 12 in. 35 20 ft. 30 ft. 50 Static Water Level 14 ft. land surface Measure 04 Pumping Level (below land surface) 22 ft. 7 hrs. Pumping at 300 g.p.m. Wellhead Completion Pitless adapter manufacturer Model Casing Protection 12 in. above grade At-grade (Environmental Wells and Borings ONLX') Grouting Information Well Grouted? X yes No Material Amount Fro bentonite 6 Sacks 0 Nearest Known Source of Contamination 200 feet East Direction Well disinfected upon completion? X yes Pump Pump Not Installed Date Installed 07/13 Manufacturer's name WESTERN Model Number 10/ICZ7 HP 30 Volt Length of drop pipe ft Capacity 250 g.p. Typ Abandoned	ft.
Static Water Level 14 ft. land surface Measure 04 Pumping Level (below land surface) 22 ft. 7 hrs. Pumping at 300 g.p.m. Wellhead Completion Pitless adapter manufacturer Model Casing Protection 12 in. above grade At-grade (Environmental Wells and Borings ONLY) Grouting Information Well Grouted? X Yes No Material Amount Fro bentonite 6 Sacks 0 Nearest Known Source of Contamination 200 feet East Direction Septic ta Well disinfected upon completion? Yes Tempon Well disinfected upon completion? Yes Tempon Well disinfected upon completion? Help and Date Installed O7/15 Manufacturer's name WESTERN Model Number 10JCZ7 HP 30 Volt Length of drop pipe ft Capacity 250 g.p. Typ Abandoned	
Pumping Level (below land surface) 22 ft. 7 hrs. Pumping at 300 g.p.m. Wellhead Completion Pitless adapter manufacturer Model Cassing Protection 12 in. above grade At-grade (Environmental Wells and Borings ONLY) Grouting Information Well Grouted? X Yes No Material Amount Fro bentonite 6 Sacks 0 Nearest Known Source of Contamination 200 feet East Direction Septic ta Well disinfected upon completion? X Yes Pump Not Installed Date Installed 07/13 Manufacturer's name WESTERN Model Number 101CZ7 HP 30 Volt Length of drop pipe ft Capacity 250 g.p. Typ Abandoned	/06/1996
Pumping Level (below land surface) 22 ft. 7 hrs. Pumping at 300 g.p.m. Wellhead Completion Pitless adapter manufacturer Model Casing Protection 12 in. above grade At-grade (Environmental Wells and Borings ONLY) Grouting Information Well Grouted? X Yes No Material Amount Fro bentonite 6 Sacks 0 Nearest Known Source of Contamination 200 feet East Direction Septic ta Well disinfected upon completion? X Yes Pump Not Installed Date Installed 07/1: Manufacturer's name WESTERN Model Number 10ICZI HP 30 Volt Length of drop pipe ft Capacity 250 g.p. Typ Abandoned	//06/1996
Wellhead Completion Pitless adapter manufacturer Casing Protection At-grade (Environmental Wells and Borings ONLY) Grouting Information Material Amount Fro bentonite Nearest Known Source of Contamination 200 feet Well disinfected upon completion? Well disinfected upon completion? Pump Not Installed Date Installed Manufacturer's name WESTERN Model Number 10ICZ7 HP 30 Volt Length of drop pipe ft Capacity 250 g.p. m.	
Wellhead Completion Pitless adapter manufacturer Casing Protection At-grade (Environmental Wells and Borings ONLY) Grouting Information Material Amount Fro bentonite Nearest Known Source of Contamination 200 feet Well disinfected upon completion? Well disinfected upon completion? Pump Not Installed Date Installed Manufacturer's name WESTERN Model Number 10ICZ7 HP 30 Volt Length of drop pipe ft Capacity 250 g.p. m.	
Pitless adapter manufacturer	
Pitless adapter manufacturer	
At-grade (Environmental Wells and Borings ONLY) Grouting Information Well Grouted? X Yes No Material Amount Fro bentonite 6 Sacks 0 Nearest Known Source of Contamination 200 feet East Direction Septic ta Well disinfected upon completion? X Yes Pump Not Installed Date Installed 07/15 Manufacturer's name WESTERN Model Number 101CZ7 HP 30 Volt Length of drop pipe ft Capacity 250 g.p. Typ Abandoned	
Material Amount Fro bentonite 6 Sacks 0 Nearest Known Source of Contamination 200 feet East Direction Septic ta Well disinfected upon completion? ▼ Yes □ Pump □ Not Installed Date Installed 07/15 Manufacturer's name WESTERN Model Number 10ICZ7 HP 30 Volt Length of drop pipe ft Capacity 250 g.p. Typ Abandoned	
Nearest Known Source of Contamination 200 feet East Direction Septic ta Well disinfected upon completion? ▼ Yes □ Pump Not Installed Date Installed 07/15 Manufacturer's name WESTERN Model Number 10ICZ7 HP 30 Volt Length of drop pipe ft Capacity 250 g.p. Typ Abandoned	Not Specified
Nearest Known Source of Contamination 200 feet East Direction Septic ta Well disinfected upon completion? X Yes Pump Not Installed Date Installed 07/15 Manufacturer's name WESTERN Model Number 101CZ7 HP 30 Volt Length of drop pipe ft Capacity 250 g.p. Typ Abandoned	
200 feet East Direction Well disinfected upon completion? ▼ Yes Pump Not Installed Date Installed 07/15 Manufacturer's name WESTERN Model Number 10JCZ7 HP 30 Volt Length of drop pipe ft Capacity 250 g.p. Typ Abandoned	ft. 30 ft.
Well disinfected upon completion? Yes	
Manufacturer's name WESTERN Model Number 10JCZ7 HP 30 Volt Length of drop pipe ft Capacity 250 g.p. Typ Abandoned	nk/drain field Type No
Length of drop pipe ft Capacity 250 g.p. Typ Abandoned	5/1996
Abandoned	<u>460</u>
	Submersible
	Yes X No
Does property have any not in use and not sealed well(s)? Variance	res _K No
	Yes No
Miscellaneous	
First Bedrock Aquifer	
Last Strat Depth to Bedrock	ft
Remarks Located by Locate Method	
System UTM - Mad83, Zone 15, Meters X	Y
Unique Number Verification Inpute I	
Angled Drill Hole	
Well Contractor	
Ingleside Engr. 27355 Licensee Business Lic. or Reg. No. N	DIEN 5
Minnesota Well Index Report 561568	DHEN, D.